



G3 - G6 SERIES SP3T - SP6T DC - 26.5 GHz MOUNTING BRACKET




FREQUENCY: GHz	DC - 2.0	2.0 - 4.0	4.0 - 8.0	8.0 - 12.4	12.4 - 18.0	18.0 - 26.5
VSWR (MAX.)	1.20:1	1.25:1	1.30:1	1.40:1	1.50:1	1.65:1
INSERTION LOSS (MAX.)	0.20	0.25	0.30	0.40	0.50	0.70
ISOLATION (MIN.)	90	80	80	70	60	50
IMPEDANCE	50 Ohms					
MECHANICAL						
CONTACT ACTUATOR SWITCHING SPEED :	BREAK BEFORE MAKE FAILSAFE, LATCHING, MOMENTARY 20 mSEC MAX.					
ELECTRICAL						
ACTUATOR VOLTAGE :	28.0, 12.0, 15.0, 24.0 Vdc					
ACTUATOR CURRENT :	CONTACT CEI					
POWER HANDLING :	200 WCW @ 1.0 GHz (STANDARD) 300 WCW @ 1.0 GHz (OPT. /P)					
ENVIRONMENTAL						
OPERATING TEMP :	-40 DEG. C TO 85 DEG. C (STANDARD) -54 DEG. C TO 90 DEG. C (OPT. /MS)					
SHOCK :	50 G's (SAWTOOTH)					
RANDOM VIBRATION :	15 G's rms (NON-OPERATING)					
LIFE :	1,000,000 CYCLES					
FINISH						
RF CAVITY :	ALUMINUM ELECTROLESS NICKEL PLATED PER MIL-C-26074, CLASS 4 (EXCEPT LOW OR ULTRA LOW IM MODELS)					
ENCLOSURE :	ALUMINUM, BLUE OR BLACK					
CONTACT :	BERYLLIUM COPPER, GOLD PLATED PER MIL-G-45204					
CONNECTOR SHELL :	CRES, PASSIVATED PER QQ-P-35 OR BRASS, ELECTROLESS NICKEL PLATED PER MIL-C-26074					
AVAILABLE OPTIONS						
INDICATOR CIRCUITRY :	CUT OFF POWER CIRCUIT					
SUPPRESSION DIODE :	D'SUB MINIATURE SERIES					
TTL LOGIC :	MS CONNECTOR OR EQUIV. (MIL-SPEC)					
BCD TTL DECODER :	LOW, ULTRA, AND SUP INTERMODULATION (IM)					

NOTE: REFERENCE FOR DIMENSIONS ONLY.
EACH MODEL NUMBER WILL HAVE A UNIQUE SCHEMATIC.
ALSO AVAILABLE WITH A D'SUB, MICRO D'SUB OR MS SERIES CONNECTOR.



* SWITCH WITH TTL LOGIC OR PWR. CONNECTOR
THIS DIMENSION TO BE 2.60 MAXIMUM

G3-G6 SERIES PART NUMBER & ORDERING INFORMATION

**1 - Switch Series**

G3	SP3T SMA
G4	SP4T SMA
G5	SP5T SMA
G6	SP6T SMA

2 - Actuator

F	FAILSAFE	R	MOMENTARY
G	FAILSAFE WITH SUPPRESSION DIODE	S	MOMENTARY WITH SUPPRESSION DIODE
H	FAILSAFE WITH INDICATOR	T	MOMENTARY WITH INDICATOR
J	FAILSAFE WITH SUPPRESSION DIODE AND INDICATOR	U	MOMENTARY WITH SUPPRESSION DIODE AND INDICATOR
L	LATCHING	Y	OTHER (SPECIFY)
M	LATCHING WITH SUPPRESSION DIODE		
N	LATCHING WITH INDICATOR		
P	LATCHING WITH SUPPRESSION DIODE AND INDICATOR		

3 - Frequency Bandwidth

1	DC - 13.0 GHz	6	DC - 6.0 GHz
2	DC - 2.0 GHz	7	DC - 26.5 GHz
3	DC - 12.4 GHz	8	DC - 20.0 GHz
4	DC - 4.0 GHz	0	OTHER (SPECIFY)
5	DC - 18.0 GHz		

4 - Voltage

1	10 - 14 Vdc (12.0 NOMINAL)	4	26 - 30 Vdc (28.0 NOMINAL)
2	13 - 17 Vdc (15.0 NOMINAL)	5	OTHER
3	22 - 26 Vdc (24.0 NOMINAL)	0	NOT REQUIRED

5 - Common Polarity

1	POSITIVE (+) COMMON
2	NEGATIVE (-) OR RETURN Vdc COMMON
0	NOT REQUIRED

6 - Power Interface

1	SOLDER TERMINAL (TOP OF SWITCH)	5	D' SUB MINIATURE SERIES (TOP OF SWITCH)
3	CONN MS3112E-XX-XXP OR EQUIV. (TOP OF SWITCH)	8	OTHER

7 - Options

1	CUT OFF POWER CIRCUIT (LATCHING ONLY)	8	OTHER (SPECIFY)
2	TTL LOGIC	9	CUSTOM (ORDER)
3	CUT OFF PWR CIRCUIT & TTL LOGIC (LATCHING ONLY)	0	NO OTHER OPTIONS REQUIRED
4	BCD TTL DECODER		

8 - Intermodulation

7	LOW PASSIVE INTERMODULATION	9	ULTRA LOW PASSIVE INTERMODULATION
8	SUPERIOR PASSIVE INTERMODULATION	0	STANDARD SWITCH


9 - Special Options (optional - leave blank if not required)

/P	HIGH TEMP, HIGH POWER CONNECTOR
/MS	EXTENDED TEMP RANGE -54 DEG C TO + 90 DEG
/MSP	HIGH TEMP, HIGH POWER CONNECTOR AND EXTENDED TEMP RANGE


SP3T/SP6T - G Series

TYPICAL NARROWBAND INSERTION LOSS PERFORMANCE CURVES


Insertion Loss (DC-4 GHz)




Insertion Loss (4-8 GHz)




Insertion Loss (8-12.4 GHz)



Insertion Loss (12.4-16 GHz)



Insertion Loss (16-20 GHz)




— TYPICAL
 — MAXIMUM TEST LIMIT


SP3T/SP6T - G Series

TYPICAL NARROWBAND RETURN LOSS PERFORMANCE CURVES


Return Loss (DC-4 GHz)




Return Loss (4-8 GHz)




Return Loss (8-12.4 GHz)



Return Loss (12.4-16 GHz)



Return Loss (16-20 GHz)




— TYPICAL
 — MAXIMUM TEST LIMIT


SP3T/SP6T - G Series

TYPICAL NARROWBAND ISOLATION PERFORMANCE CURVES


Isolation (DC-4 GHz)




Isolation (4-8 GHz)




Isolation (8-12.4 GHz)



Isolation (12.4-16 GHz)



Isolation (16-20 GHz)



— TYPICAL
 — MAXIMUM TEST LIMIT